

MARINA II

Interior Round Semi-Surface Mount




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION


- LED:** High efficiency mid-power LEDs are field serviceable.
- Lower Output:** Lamping code ending with LO features lower lumen output.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.
- Shade:** Standard white fabric shade with integral satin white diffuser. Custom shapes, sizes, and colors available.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Modifications:** Consult factory for lamping or cluster options.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-3742-				L55-		W-		A		
MODEL NO.				LAMPING			SHADE		OPTIONS	
GL-3740	W in 14" 5lbs 2.25kg	D in 9.5" mm 240	mm 355	IN3. 3MED	L10. 1LED30 L15. 1LED35 L14. 1LED40	LL10. 1LED30LO LL15. 1LED35LO LL14. 1LED40LO	W White C Cream BL Blue BK Black S Stone R Red	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.		
GL-3741	W in 18" 5lbs 2.25kg	D in 9.5" mm 265	mm 460	IN3. 3MED	L10. 1LED30 L15. 1LED35 L14. 1LED40	LL10. 1LED30LO LL15. 1LED35LO LL14. 1LED40LO	W White C Cream BL Blue BK Black S Stone R Red			
GL-3742	W in 24" 15lbs 7kg	D in 11.5" mm 295	mm 610	IN3. 3MED	L50. 5LED30 L55. 5LED35 L54. 5LED40	LL50. 5LED30LO LL55. 5LED35LO LL54. 5LED40LO	Washable: WW White WC Cream WLG Lt Gray WGR Gray WBK Black WR Red WBL Blue			
GL-3743	W in 30" 18lbs 8kg	D in 12.5" mm 320	mm 760	IN3. 3MED	L50. 5LED30 L55. 5LED35 L54. 5LED40	LL50. 5LED30LO LL55. 5LED35LO LL54. 5LED40LO				
GL-3744	W in 36" 20lbs 9kg	D in 13.5" mm 340	mm 915	IN6. 6MED	L80. 8LED30 L85. 8LED35 L84. 8LED40	LL80. 8LED30LO LL85. 8LED35LO LL84. 8LED40LO				
GL-3745	W in 48" 25lbs 11.5kg	D in 15.5" mm 395	mm 1220	IN6. 6MED	L80. 8LED30 L85. 8LED35 L84. 8LED40	LL80. 8LED30LO LL85. 8LED35LO LL84. 8LED40LO	Shade options may vary based on availability. Consult Finish Guide at glighting.com for current options.			

All Dimensions are nominal.

Shade



Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Lamp	Type	Lamp Base	Code	Lamp	Total Wattage	Delivered Lumens	Kelvin	CRI
IN3,IN6	MED	A-19	Medium 120V	LL50	5LED30LO	39W	4462	3000	+90
		Total	Delivered	LL55	5LED35LO	39W	4462	3500	+90
		Wattage	Lumens	LL54	5LED40LO	39W	4462	4000	+90
			Kelvin	L50	5LED30	65W	7436	3000	+90
LL10	1LED30LO	17 W	1825	L55	5LED35	65W	7436	3500	+90
LL15	1LED35LO	17 W	1825	L54	5LED40	65W	7436	4000	+90
LL14	1LED40LO	17 W	1825	L80	8LED30LO	63W	7126	3000	+90
L10	1LED30	27 W	3008	LL85	8LED35LO	63W	7126	3500	+90
L15	1LED35	27 W	3008	LL84	8LED40LO	63W	7126	4000	+90
L14	1LED40	27 W	3008	L80	8LED30	105W	12248	3000	+90
				L85	8LED35	105W	12248	3500	+90
				L84	8LED40	105W	12248	4000	+90

Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.