

# MEDI

## Interior Pendant




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- Uplight:** Optional uplight is wired on a second circuit. Standard satin white top lens.
- LED Dimming:** Standard 1% 0-10V dimming.
- Cable Hanger Option:** Standard 150" cable and white cord for on-site adjustability.
- Canopy:** Matches outer fixture finish. Hanger 3 & 4 with A-O lamping option includes 10.125" dia by 2.625" H spinning. V, W, X lamping includes 12" dia by 2" H.
- Driver:** Max remote driver installation distance 25ft from fixture body.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Inner Finish:** Inner finish matches outer finish.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:								
GL-2356-		E-	K-	BLK-	MO-	1-	A	038
MODEL NO.	LAMPING	UPLIGHT	OUTER FINISH	INNER FINISH	HANGER	OPTIONS	OVERALL HEIGHT	
<b>GL-2355</b> 8lbs Win 16" 3.6kg B in 7 3/8" H in 38"	<b>A.</b> 1LED30 <b>B.</b> 1LED35 <b>C.</b> 1LED40 <b>D.</b> 1LED30 <b>E.</b> 1LED35 <b>F.</b> 1LED40	<b>NA.</b> NONE <b>J.</b> 1UPLED30 <b>K.</b> 1UPLED35 <b>L.</b> 1UPLED40 <b>M.</b> 1UPLED30 <b>N.</b> 1UPLED35 <b>O.</b> 1UPLED40	<b>Standard:</b> Powder Coat <b>BLK-</b> Black <b>BL-</b> Blue <b>GR-</b> Gray <b>LG-</b> Light Gray <b>BE-</b> Beige <b>PAB-</b> Antique Brass <b>PA-</b> Painted Aluminum <b>PTC-</b> Painted Copper <b>WH-</b> White <b>DBZ-</b> Dark Bronze <b>NSN-</b> New Satin Nickel <b>BRN-</b> Brown <b>RD-</b> Red <b>CH-</b> Champagne <b>RG-</b> Reed Green <b>SG-</b> Sungold <b>GM-</b> Gun Metal <b>POR-</b> Oil Rubbed Bronze <b>PG-</b> Pine Green <b>DO-</b> Deep Orange <b>PV-</b> Purple Violet <b>NB-</b> Navy Blue	<b>Standard:</b> MO-Matches Outer Finish Liquid Paint <b>WH-</b> White <b>BLK-</b> Black <b>GL-</b> Gold	<b>1.</b> Stem Mount Remote Driver  Drivers mounted remotely <b>2.</b> Cable Mount Remote Driver  Drivers mounted remotely <b>3.</b> Stem Mount Oversized Canopy  Drivers mounted inside oversized canopy <b>4.</b> Cable Mount Oversized Canopy  Drivers mounted inside oversized canopy	<b>A.</b> No Options <b>BC.</b> Black Cord Fixture supplied with black power cord. <b>DM.</b> DMX Dimming <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. Downlight only.	Specify overall height in inches for hanger styles 1 & 3.	
								<b>GL-2356</b> 10lbs Win 24" 4.5kg B in 11 9/16" H in 42"
<b>GL-2357</b> 15lbs Win 32" 6.8kg B in 15 11/16" H in 46"								

All Dimensions are nominal.

### Light Source Definition

Downlight Output						Uplight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	1LED30	15W	1538	3000	80	J	1UPLED30	8W	866	3000	80
B	1LED35	15W	1538	3500	80	K	1UPLED35	8W	866	3500	80
C	1LED40	15W	1538	4000	80	L	1UPLED40	8W	866	4000	80
D	1LED30	26W	2637	3000	80	M	1UPLED30	12W	1213	3000	80
E	1LED35	26W	2637	3500	80	N	1UPLED35	12W	1213	3500	80
F	1LED40	26W	2637	4000	80	O	1UPLED40	12W	1213	4000	80
G	1LED30	39W	3956	3000	80						
H	1LED35	39W	3956	3500	80						
I	1LED40	39W	3956	4000	80						
V	1LED30	68W	6009*	3000	80						
W	1LED35	68W	6009*	3500	80						
X	1LED40	68W	6009*	4000	80						

\*Projected

Universal Voltage unless otherwise specified.  
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

