

MESA

Indoor Pendant




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency +90CRI mid-power LEDs are field serviceable.
- LED Dimming:** 1% 0-10V dimming standard with LED lamping option.
- Body:** Body formed with 18ga steel.
- Canopy:** Low profile. Mounted on flat or sloped ceilings up to 40°.
- Acrylic:** UL-94 HB Flame Class rated.
- Modifications:** Consult factory for lamping, cluster, or sizing options.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
GL-2620 21lbs W in 24" mm 610 10kg D in 12 1/4" mm 310 H in 36" mm 915	L60. 6LED30 L65. 6LED35 L64. 6LED40	IN4. 4MED Standard: W. White Opal Optional: S. Satin White	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze PG- Pine Green DO- Deep Orange PV- Purple Violet NB- Navy Blue Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone	1. Stem 2. Cable 3. Arms 4. Stem Cluster Custom lengths available. For heights longer than standard, additional length will be added to top stem.	A. No Options B. Damp Location Available in powder coat finish. EL. Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. W. White Opal Top Lens INC only C. Clear Top Lens INC only P. Perforated Top Lens INC only	Standard overall height shown by model no. For custom overall height, specify in inches.
GL-2621 28lbs W in 30" mm 760 13kg D in 15 1/4" mm 390 H in 40" mm 1020	L80. 8LED30 L85. 8LED35 L84. 8LED40	IN4. 4MED Acrylic is UL-94 HB Flame Class rated.				
GL-2622 37lbs W in 36" mm 915 17kg D in 18 1/8" mm 460 H in 45" mm 1140	L120. 12LED30 L125. 12LED35 L124. 12LED40	IN4. 4MED IN6. 6MED				
GL-2623 52lbs W in 46" mm 1170 24kg D in 22 3/4" mm 580 H in 50" mm 1270	L120. 12LED30 L125. 12LED35 L124. 12LED40	IN6. 6MED IN8. 8MED				

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Light Source Definition

Code	Total Wattage	Kelvin	Board Lumens	CRI	Code	Lamp	Type	Lamp Base
L60	65	3000	11370	+90	IN4, IN6, IN8	Med	A-19	Medium 120V
L65	65	3500	11370	+90				
L64	65	4000	11370	+90				
L80	105	3000	15160	+90				
L85	105	3500	15160	+90				
L84	105	4000	15160	+90				
L120	157	3000	22740	+90				
L125	157	3500	22740	+90				
L124	157	4000	22740	+90				

Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.