

# OCULUS TUNABLE WHITE

## Interior Surface Mount



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**Tunable White:** LED option (TW) features tunable white technology that adjusts from 6500K-2700K. For proper control, fixture needs two 0-10V dimming controls.


**LED Tuning:** CCT tunable using 0-10V wall control. TRIAC, DALI, or DMX available upon request.

**LED Dimming:** Intensity adjustable using 1% 0-10V wall control. TRIAC, DALI, or DMX available upon request.

**Acrylic:** Satin white seamless acrylic is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat. Spinning interior painted textured white.

**Surge Protection:** External surge protection provided as standard.



SAMPLE CATALOG NUMBER: GL-3641-		TW5-	NSN-	A
MODEL NO.		LAMPING	FINISH	OPTIONS
<b>GL-3640</b>	W in 26" mm 660 8lbs B in 7 1/2" mm 190 3.5kg	<b>TW4</b>	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue  Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	<b>A. No Options</b> <b>EL. Emergency LED</b> Remote mount up to 10' from light source in controlled environment with an area temperature range of 32"-131°F. Specify 120 or 277 voltage.
<b>GL-3641</b>	W in 37" mm 940 10lbs B in 7 1/2" mm 190 4.5kg	<b>TW5</b>	Not available in standard white finish	

All Dimensions are nominal.

### Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
TW4	56W	4310	2700-6500
TW5	72W	5320	2700-6500

Universal Voltage unless otherwise specified.