

ODYSSEY

Exterior Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.

LED Dimming: Standard 1% 0-10V dimming.

Listing: ETL listed for wet locations.


Canopy: Matches fixture finish. Hanger 3 includes 10.125" dia by 2.625" H spinning.



Driver: Max remote driver installation distance 25ft from fixture body.

Acrylic: Acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-5380-					
GL-5380-					
MODEL NO.	E-	BLK-	1-	A	038
MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-5380 W 19 5/8" 8lbs B 10" 3.6kg H 38"	A. 1LED30 B. 1LED35 C. 1LED40 D. 1LED30 E. 1LED35 F. 1LED40 G. 1LED30 H. 1LED35 I. 1LED40	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone	1. Stem Mount Remote Driver  Drivers mounted remotely 3. Stem Mount Oversized Canopy  Drivers mounted inside oversized canopy	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage	Specify overall height in inches for hanger styles 1 & 3.

All Dimensions are nominal.

Light Source Definition

Downlight Output						
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	
A	1LED30	15W	1538	3000	80	
B	1LED35	15W	1538	3500	80	
C	1LED40	15W	1538	4000	80	
D	1LED30	26W	2637	3000	80	
E	1LED35	26W	2637	3500	80	
F	1LED40	26W	2637	4000	80	
G	1LED30	39W	3956	3000	80	
H	1LED35	39W	3956	3500	80	
I	1LED40	39W	3956	4000	80	

Universal Voltage unless otherwise specified.
 Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

