

ROCKFORD

Indoor Pendant





9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs are field serviceable.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.
- Down Light:** 90CRI 17 watt 2000 lumen module. Lamping code ending with "DL" includes downlight.
- Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.
- Canopy:** Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.
- Cable Hanger Option:** Supplied with standard 72" white cord and cable. Field adjustable.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Modifications:** Consult factory for lamping or cluster options.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2425-	A-	W-	NSN-	1-	A-	34
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
GL-2425 12lbs W in 11 1/8" mm 280 6 kg B in 26" mm 635 H in 34" mm 890 Fixture does not include downlight	U. 4LED30 V. 4LED35 W. 4LED40	Standard: S. Satin White Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone	1. Stem Remote driver. 2. Cable Standard white power cord. Remote driver.	A. No Options BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Standard overall height shown by model no. For custom overall height, specify in inches.
GL-2426 21lbs W in 11 1/8" mm 280 10 kg B in 33 3/8" mm 850 H in 44" mm 1120 Fixture includes downlight	AA. 4LED30DL BB. 4LED35DL CC. 4LED40DL			3. Oversized with Stem 12" Canopy 4. Oversized with Cable Standard white power cord. 12" Canopy.	Hanger options 1&2 supplied with remote driver box.	

All dimensions are nominal.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin	Code	*Total Wattage	*Delivered Lumens	Kelvin
U	51W	5556	3000	AA	68W	7248	3000
V	51W	5556	3500	BB	68W	7248	3500
W	51W	5556	4000	CC	68W	7248	4000

Universal Voltage unless otherwise specified. *Includes downlight wattage (17W) and lumen output (1692lm)