

SIDNEY 3"

Indoor Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.

LED Dimming: Standard 0-10V dimming.

Down Light: 80CRI 8 watt 900 lumen module. Lamping code ending with "DL" includes downlight. Fixture supplied with 40deg downlight optic standard. 80deg downlight optic optional. Down light wired on a second circuit.


Acrylic: Satin white seamless acrylic is UL-94 HB Flame Class rated.

Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord.

Cable Hanger Option: Supplied with standard 72" white cord. Field adjustable.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:

GL-2670-	B-	S-	WH-	1-	A-	038
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
GL-2670 W 3" in 75 mm B 13 1/2" in 340 mm 5lbs H 38" in 965 mm 2.2kg	A. 14LED30 B. 14LED35 C. 14LED40 M. 14LED30DL N. 14LED35DL O. 14LED40DL	Standard: S Satin White Acrylic is UL-94 HB Flame Class rated.	Standard: BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone	1. Stem Remote driver. 2. Cord Standard white power cord. Remote driver. 3. Oversized with Stem 12" Canopy 4. Oversized with Cord Standard white power cord. 12" Canopy.	A. No Options EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord Fixture supplied with 150" standard white cord or optional black cord. DL80. 80deg Optic Fixture supplied with 80degree downlight optic. For fixtures specified with downlight lamping options only.	Stem mount only - Specify overall height in inches. Standard overall height shown by model no.
GL-2671 W 3" in 75 mm B 25 1/2" in 650 mm 10lbs H 44" in 1120mm 4.5kg	D. 26LED30 E. 26LED35 F. 26LED40 P. 26LED30DL Q. 26LED35DL R. 26LED40DL					
GL-2672 W 3" in 75 mm B 37 1/2" in 950 mm 15lbs H 62" in 1575mm 6.8kg	G. 38LED30 H. 38LED35 I. 38LED40 S. 38LED30DL T. 38LED35DL U. 38LED40DL					
GL-2673 W 3" in 75 mm B 49 1/2" in 1260 mm 20lbs H 67" in 1700 mm 9kg	J. 50LED30 K. 50LED35 L. 50LED40 V. 50LED30DL W. 50LED35DL X. 50LED40DL					

All dimensions are nominal.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin	Code	*Total Wattage	*Delivered Lumens	Kelvin
A	16W	1323	3000	M	23W	2223	3000
B	16W	1323	3500	N	23W	2223	3500
C	16W	1323	4000	O	23W	2223	4000
D	28W	2744	3000	P	35W	3644	3000
E	28W	2744	3500	Q	35W	3644	3500
F	28W	2744	4000	R	35W	3644	4000
G	42W	4328	3000	S	49W	5228	3000
H	42W	4328	3500	T	49W	5228	3500
I	42W	4328	4000	U	49W	5228	4000
J	60W	6042	3000	V	67W	6942	3000
K	60W	6042	3500	W	67W	6942	3500
L	60W	6042	4000	X	67W	6942	4000

*Includes downlight wattage (8W) and lumen output (900lm) Universal Voltage unless otherwise specified.

