

SIDNEY 8" LED

Interior Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.

Down Light: 90CRI 17 watt 2000 lumen module. Lamping code ending with "DL" includes downlight.

Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.


Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.

Cable Hanger Option: Supplied with standard 72" white cord and cable. Field adjustable.

Finish: Highly durable oven cured no VOC premium powder coat.

Modifications: Consult factory for lamping or cluster options.

Surge Protection: External surge protector provided as standard.



Standard White Power Cord



SAMPLE CATALOG NUMBER:						
GL-2665-	H-	W-	NSN-	1-	A-	038
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
GL-2665 Win 8" mm 205 B in 26" mm 660 15lbs H in 38" mm 965 7kg Fixture does not include downlight	G. 4LED30 H. 4LED35 I. 4LED40	Standard: S Satin White Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone	1. Stem Remote driver. 2. Cable Standard white power cord. Remote driver. 3. Oversized with Stem 12" Canopy 4. Oversized with Cable Standard white power cord. 12" Canopy.	A. No Options BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Stem mount only - Specify overall height in inches. Standard overall height shown by model no.
GL-2666 Win 8" mm 205 B in 33 3/8" mm 850 17lbs H in 44" mm 1120 7.7kg Fixture includes downlight	J. 4LED30DL K. 4LED35DL L. 4LED40DL					
GL-2667 Win 8" mm 205 B in 51 3/4" mm 1315 25lbs H in 62" mm 1575 11.3kg Fixture does not include downlight	M. 8LED30 N. 8LED35 O. 8LED40					
GL-2668 Win 8" mm 205 B in 57" mm 1450 27lbs H in 67" mm 1700 12.25kg Fixture includes downlight	P. 8LED30DL Q. 8LED35DL R. 8LED40DL					

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Delivered Kelvin	Code	*Total Wattage	*Delivered Lumens	*Delivered Kelvin
G	37W	4601	3000	J	54W	6293	3000
H	37W	4601	3500	K	54W	6293	3500
I	37W	4601	4000	L	54W	6293	4000
M	76W	9053	3000	P	93W	10745	3000
N	76W	9053	3500	Q	93W	10745	3500
O	76W	9053	4000	R	93W	10745	4000

Universal Voltage unless otherwise specified.

*Includes downlight wattage (17W) and lumen output (1692lm)

