

SONOMA II

Interior Pendant




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency +90CRI mid-power LEDs are field serviceable.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.
- Shade:** Standard white fabric shade with integral satin white diffuser. Custom shapes, sizes, and colors available.
- Acrylic:** Satin white acrylic bottom diffuser is UL-94 HB Flame Class rated.
- Canopy:** Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.
- Cable Hanger Option:** Supplied with standard 72" white cord and cable. Field adjustable.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Modifications:** Consult factory for lamping or cluster options.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:							
GL-2905-		L55-	W-	NSN-	1-	A-	045
MODEL NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT	
GL-2905 W in 30 1/8" 15lbs B in 34" 7kg H in 45"	L50. 5LED30 L55. 5LED35 L54. 5LED40 IN4. 4MED*	W White C Cream BL Blue BK Black S Stone R Red Washable: WW White WC Cream WLG Lt Gray WGR Gray WBK Black WR Red WBL Blue <small>Shade options may vary based on availability. Consult Finish Guide at glighting.com for current options.</small>	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone	1. Stem Mount Drivers mounted integrally 2. Cable Mount Drivers mounted integrally	A. No Options BC. Black Cord <small>Fixture supplied with black power cord.</small> LC. 150" Cord & Cable <small>Fixture supplied with 150" of cable and standard white cord or optional black cord.</small> EL. Emergency LED <small>Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.</small>	Standard 45" overall height. Available up to 93". For custom overall height, contact factory.	

All Dimensions are nominal. 120V only*

Shade

Standard

White Cream Blue Stone Red Black

Washable - Trilam

White Cream Light Gray Gray Black Red Blue

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Total Wattage	Board Lumens	Kelvin	CRI	Code	Lamp	Lamp Base
L50	65W	9750	3000	+90	IN4	A-19	Medium
L55	65W	9750	3500	+90			
L54	65W	9750	4000	+90			

Universal Voltage unless otherwise specified.