

STONE

Interior Surface Mount




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- LED Dimming:** Standard 1% 0-10V dimming.
- Driver:** Integral in fixture body. Remote driver required for V,W,X lamping options.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-3370-			
MODEL NO.	E- LAMPING	BLK- FINISH	A OPTIONS
GL-3370 W 21 in 8lbs B 11 1/4 in 3.6kg	A. 1LED30 B. 1LED35 C. 1LED40 D. 1LED30 E. 1LED35 F. 1LED40 G. 1LED30 H. 1LED35 I. 1LED40 V. 1LED30* W. 1LED35* X. 1LED40*	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze PG- Pine Green DO- Deep Orange PV- Purple Violet NB- Navy Blue Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone	A. No Options DM. DMX Dimming Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
	*Remote Driver only.		

All Dimensions are nominal.

Light Source Definition

Downlight Output						
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	
A	1LED30	15W	1538	3000	80	
B	1LED35	15W	1538	3500	80	
C	1LED40	15W	1538	4000	80	
D	1LED30	26W	2637	3000	80	
E	1LED35	26W	2637	3500	80	
F	1LED40	26W	2637	4000	80	
G	1LED30	39W	3956	3000	80	
H	1LED35	39W	3956	3500	80	
I	1LED40	39W	3956	4000	80	
V	1LED30	68W	6009*	3000	80	
W	1LED35	68W	6009*	3500	80	
X	1LED40	68W	6009*	4000	80	*Projected

Universal Voltage unless otherwise specified.
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

