

TAHOE II

Interior Square Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.

Lower Output: Lamping code ending with LO features lower lumen output.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.

Shade: Standard white fabric shade with integral satin white diffuser.

Custom shapes, sizes, and colors available.


Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.













Cable Hanger Option: Supplied with standard 72" white cord and cable. Field adjustable.

Finish: Highly durable oven cured no VOC premium powder coat.

Modifications: Consult factory for lamping or cluster options.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:								
GL-2732-		L55-		W-	NSN-	1-	A-	023
MODEL NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT		
GL-2730 W in 14" 5lbs D in 9.5" 2.25kg H in 21"	L10. 1LED30 L15. 1LED35 L14. 1LED40 IN3. 3MED	LL10. 1LED30LO LL15. 1LED35LO LL14. 1LED40LO	W White C Cream BL Blue BK Black S Stone R Red	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue	1. Stem  5. Cord & Cable  Supplied with white cord with hanger option 5.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.	
GL-2731 W in 18" 5lbs D in 9.5" 2.25kg H in 21"	L10. 1LED30 L15. 1LED35 L14. 1LED40 IN3. 3MED	LL10. 1LED30LO LL15. 1LED35LO LL14. 1LED40LO	W White C Cream BL Blue BK Black S Stone R Red	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue	1. Stem  5. Cord & Cable  Supplied with white cord with hanger option 5.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.	
GL-2732 W in 24" 15lbs D in 11.5" 7kg H in 23"	L50. 5LED30 L55. 5LED35 L54. 5LED40 IN3. 3MED	LL50. 5LED30LO LL55. 5LED35LO LL54. 5LED40LO	Washable: WW White WC Cream WLG Lt Gray WGR Gray WBK Black WR Red WBL Blue	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue	1. Stem  5. Cord & Cable  Supplied with white cord with hanger option 5.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.	
GL-2733 W in 30" 18lbs D in 12.5" 8kg H in 23"	L50. 5LED30 L55. 5LED35 L54. 5LED40 IN3. 3MED	LL50. 5LED30LO LL55. 5LED35LO LL54. 5LED40LO	Washable: WW White WC Cream WLG Lt Gray WGR Gray WBK Black WR Red WBL Blue	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue	1. Stem  5. Cord & Cable  Supplied with white cord with hanger option 5.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.	
GL-2734 W in 36" 20lbs D in 13.5" 9kg H in 25"	L80. 8LED30 L85. 8LED35 L84. 8LED40 IN6. 6MED	LL80. 8LED30LO LL85. 8LED35LO LL84. 8LED40LO	Shade options may vary based on availability. Consult Finish Guide at glighting.com for current options.	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue	1. Stem  5. Cord & Cable  Supplied with white cord with hanger option 5.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.	
GL-2735 W in 48" 25lbs D in 15.5" 11.5kg H in 27"	L80. 8LED30 L85. 8LED35 L84. 8LED40 IN6. 6MED	LL80. 8LED30LO LL85. 8LED35LO LL84. 8LED40LO	Shade options may vary based on availability. Consult Finish Guide at glighting.com for current options.	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue	1. Stem  5. Cord & Cable  Supplied with white cord with hanger option 5.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.	

All Dimensions are nominal.

Shade

Standard

White Cream Blue Stone Red Black

Washable - Trilam

White Cream Light Gray Gray Black Red Blue

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Lamp	Type	Lamp Base	Code	Lamp	Total Wattage	Delivered Lumens	Kelvin	CRI
IN3,IN6	MED	A-19	Medium 120V	LL50	5LED30LO	39W	4462	3000	+90
				LL55	5LED35LO	39W	4462	3500	+90
				LL54	5LED40LO	39W	4462	4000	+90
				L50	5LED30	65W	7436	3000	+90
				L55	5LED35	65W	7436	3500	+90
				L54	5LED40	65W	7436	4000	+90
				LL80	8LED30LO	63W	7126	3000	+90
				LL85	8LED35LO	63W	7126	3500	+90
				LL84	8LED40LO	63W	7126	4000	+90
				L80	8LED30	105W	12248	3000	+90
				L85	8LED35	105W	12248	3500	+90
				L84	8LED40	105W	12248	4000	+90

Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.