

# TRIBUNE

## Indoor ADA Sconce



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**Body:** Formed .050 aluminum body with 1/4" x 1/2" aluminum rails and 1/2"sq decorative bars.

**Acrylic:** Cylinder is UL-94 HB Flame Class rated. Top and bottom lens standard.


**Standard Finishes:** Highly durable oven cured no VOC premium powder coat.

**LED:** High efficiency +90CRI mid-power LEDs are field serviceable.

**LED Dimming:** 1% 0-10V dimming standard with LED lamping option.

**Modified:** Contact factory for modified lengths, lamping and decorative fronts.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:				
GL-4430-	G-	W-	BLK-	A
MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)
<b>GL-4430</b> W in 7 1/4" mm 185 H in 18" mm 460 5lbs 2.3kg D in 4" mm 100	<b>F.</b> 13LED30 <b>G.</b> 13LED35 <b>H.</b> 13LED40	<b>Standard:</b> W. White Opal  <b>Optional:</b> S. Satin White  Acrylic is UL-94 HB Flame Class rated.	<b>Standard:</b> Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>WH</b> -White <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze <b>PG</b> -Pine Green <b>DO</b> -Deep Orange <b>PV</b> -Purple Violet <b>NB</b> -Navy Blue  <b>Textured Powder</b> <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBZ</b> -Textured Bronze <b>TST</b> -Stone	<b>A.</b> No Options <b>B.</b> Damp Location <b>EL.</b> Emergency LED Consult factory. Must be remotely mounted in a controlled environment with an area temperature range of 32°- 131°F. <b>F.</b> LED Up Light 4000K Metal cap standard with option. Consult factory for dimming. <b>G.</b> LED Down Light 4000K Metal cap standard with option. Consult factory for dimming. <b>H.</b> LED Up Light 3000K Metal cap standard with option. Consult factory for dimming. <b>I.</b> LED Down Light 3000K Metal cap standard with option. Consult factory for dimming.

All dimensions are nominal.

### Light Source Definition

Lamp	LED	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
13LED30	13W	+90	50000	1192	3000
13LED35	13W	+90	50000	1192	3500
13LED40	13W	+90	50000	1192	4000
UP/DOWN	4W SPOT LIGHT	80	35000	260	3000 or 4000

Universal Voltage unless otherwise specified.  
Contact factory for availability of other lamp configurations.

