

CONE

Exterior Surface Mount



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.

LED Dimming: Standard 1% 0-10V dimming.


Listing: ETL listed for wet locations.

Driver: Integral in fixture body.

Acrylic: Acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:

GL-9350-

MODEL NO.	E- LAMPING	BLK- FINISH	A OPTIONS
GL-9350 8lbs W in 16" 3.6kg H in 11"	A. 1LED30 B. 1LED35 C. 1LED40 D. 1LED30 E. 1LED35 F. 1LED40	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze PG- Pine Green DO- Deep Orange PV- Purple Violet NB- Navy Blue Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-9351 10lbs W in 24" 4.5kg H in 15 3/8"	G. 1LED30 H. 1LED35 I. 1LED40 J. 1LED30 K. 1LED35 L. 1LED40 M. 1LED30 N. 1LED35 O. 1LED40		

All Dimensions are nominal.

Light Source Definition

Code	LED	Downlight Output		Kelvin	CRI
		Total Wattage	Delivered Lumens		
A	1LED30	17W	1534	3000	80
B	1LED35	17W	1534	3500	80
C	1LED40	17W	1534	4000	80
D	1LED30	24W	2148	3000	80
E	1LED35	24W	2148	3500	80
F	1LED40	24W	2148	4000	80
G	1LED30	15W	1361	3000	80
H	1LED35	15W	1361	3500	80
I	1LED40	15W	1361	4000	80
J	1LED30	26W	2334	3000	80
K	1LED35	26W	2334	3500	80
L	1LED40	26W	2334	4000	80
M	1LED30	39W	3501	3000	80
N	1LED35	39W	3501	3500	80
O	1LED40	39W	3501	4000	80

Universal Voltage unless otherwise specified.
Fixture tested with white finish. Non-white finishes will reduce lumen output.

