

# MARINA II TUNABLE WHITE

## Interior Round Pendant



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**Tunable White:** LED option (TW) features tunable white technology that adjusts from 6500K-2700K. For proper control, fixture needs two 0-10V dimming controls.

**LED Tuning:** CCT tunable using 0-10V wall control. TRIAC, DALI, or DMX available upon request.

**LED Dimming:** Intensity adjustable using 1% 0-10V wall control. TRIAC, DALI, or DMX available upon request.


**Shade:** Standard white fabric shade with integral satin white diffuser.

**Canopy:** Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.

**Cable Hanger Option:** Supplied with standard 72" white cord and cable. Field adjustable.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2742-	TW5-	W-	NSN-	1-	A-	023
MODEL NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
<b>GL-2742</b> W in 24" 15lbs D in 11.5" 7kg H in 23"	<b>TW5</b>	<b>W</b> White <b>C</b> Cream <b>BL</b> Blue <b>BK</b> Black <b>S</b> Stone <b>R</b> Red	<b>Standard:</b> Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>WH</b> -White <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze <b>PG</b> -Pine Green <b>DO</b> -Deep Orange <b>PV</b> -Purple Violet <b>NB</b> -Navy Blue  <b>Textured Powder</b> <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBZ</b> -Textured Bronze <b>TST</b> -Stone	<b>1. Stem</b>  <b>5. Cord &amp; Cable</b>  Supplied with white cord with hanger option 5.	<b>A. No Options</b> <b>BC. Black Cord</b> Fixture supplied with black power cord. <b>EL. Emergency LED</b> Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. <b>LC. 150" Cord &amp; Cable</b> Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.
<b>GL-2743</b> W in 30" 18lbs D in 12.5" 8kg H in 24"	<b>TW5</b>	Washable: <b>WW</b> White <b>WC</b> Cream <b>WLG</b> Lt Gray				
<b>GL-2744</b> W in 36" 20lbs D in 13.5" 9kg H in 25"	<b>TW8</b>	<b>WGR</b> Gray <b>WBK</b> Black <b>WR</b> Red <b>WBL</b> Blue	Shade options may vary based on availability. Consult Finish Guide at glighting.com for current options.			
<b>GL-2745</b> W in 48" 25lbs D in 15.5" 11.5kg H in 27"	<b>TW8</b>					

All Dimensions are nominal.

### Shade

**Standard**

White    Cream    Blue    Stone    Red    Black

**Washable - Trilam**

White    Cream    Light Gray    Gray    Black    Red    Blue

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

### Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
TW5	72	7736	2700-6500
TW8	114	12248	2700-6500

Universal Voltage unless otherwise specified.