

# MEDI

## Exterior Surface Mount



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency mid-power LEDs.

**LED Dimming:** Standard 1% 0-10V dimming.


**Listing:** ETL listed for wet locations.

**Driver:** Integral in fixture body.

**Acrylic:** Acrylic is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-9356-			
MODEL NO.	E-	BLK-	A
MODEL NO.	LAMPING	FINISH	OPTIONS
<b>GL-9355</b> 8lbs Win 16" 3.6kg H in 7 3/8"	<b>A.</b> 1LED30 <b>B.</b> 1LED35 <b>C.</b> 1LED40 <b>D.</b> 1LED30 <b>E.</b> 1LED35 <b>F.</b> 1LED40 <b>G.</b> 1LED30 <b>H.</b> 1LED35 <b>I.</b> 1LED40	<b>Standard:</b> Powder Coat <b>BLK-</b> Black <b>BL-</b> Blue <b>GR-</b> Gray <b>LG-</b> Light Gray <b>BE-</b> Beige <b>PAB-</b> Antique Brass <b>PA-</b> Painted Aluminum <b>PTC-</b> Painted Copper <b>WH-</b> White <b>DBZ-</b> Dark Bronze <b>NSN-</b> New Satin Nickel <b>BRN-</b> Brown <b>RD-</b> Red <b>CH-</b> Champagne <b>RG-</b> Reed Green <b>SG-</b> Sungold <b>GM-</b> Gun Metal <b>POR-</b> Oil Rubbed Bronze <b>PG-</b> Pine Green <b>DO-</b> Deep Orange <b>PV-</b> Purple Violet <b>NB-</b> Navy Blue  <b>Textured Powder</b> <b>TLV-</b> Light Verdigris <b>TWH-</b> Textured White <b>TBL-</b> Textured Black <b>TS-</b> Textured Silver <b>TBZ-</b> Textured Bronze <b>TST-</b> Stone	<b>A.</b> No Options  <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
<b>GL-9356</b> 10lbs Win 24" 4.5kg H in 11 9/16"			
<b>GL-9357</b> 15lbs Win 32" 6.8kg H in 15 11/16"			

All Dimensions are nominal.

### Light Source Definition

Downlight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	1LED30	15W	1538	3000	80
B	1LED35	15W	1538	3500	80
C	1LED40	15W	1538	4000	80
D	1LED30	26W	2637	3000	80
E	1LED35	26W	2637	3500	80
F	1LED40	26W	2637	4000	80
G	1LED30	39W	3956	3000	80
H	1LED35	39W	3956	3500	80
I	1LED40	39W	3956	4000	80

Universal Voltage unless otherwise specified.  
Fixture tested with white finish. Non-white finishes will reduce lumen output.

