

CAPRICORN

Indoor Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.

LED Dimming: Standard 1% 0-10V dimming with LED lamping option.


Canopy: Low profile. May be mounted on flat or sloped ceilings up to 40°.

Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.

Finial Option required with LED lamping.



SAMPLE CATALOG NUMBER:							
GL-2072-		IN6	S-	NSN-	1-	A-	038
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT	
GL-2070 14lbs B in 18" mm 460 6 kg D in 6" mm 150 H in 29" mm 740	IN3. 3MED L50. 5LED30* L55. 5LED35* L54. 5LED40* <small>*Finial option required for LED.</small>	Standard: W. White Opal Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue	1. Stem 	A. No Options F1. Add Finial F2. Add Finial 	Standard overall height shown by model no. For custom overall height, specify in inches.	
GL-2071 21lbs B in 24" mm 610 10 kg D in 6 1/2" mm 165 H in 34" mm 865	IN3. 3MED L60. 6LED30* L65. 6LED35* L64. 6LED40* <small>*Finial option required for LED.</small>		2. Cable 	B. Damp Location Available in powder coat or Satin Aluminum finish. EL. Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.			
GL-2072 29lbs B in 30" mm 760 13kg D in 7" mm 180 H in 38" mm 965	IN6. 6MED L90. 9LED30* L95. 9LED35* L94. 9LED40* <small>*Finial option required for LED.</small>		3. Arms 	Multi-circuiting available upon request.			
GL-2073 37lbs B in 38" mm 965 17kg D in 9" mm 230 H in 42" mm 1070	IN6. 6MED L120. 12LED30* L125. 12LED35* L124. 12LED40* <small>*Finial option required for LED.</small>		4. Stem Cluster 				
				<small>Custom lengths available. For heights longer than standard, additional length will be added to top stem.</small>			

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Lamp Definition

Code	Lamp Type	Lamp Base	Total Wattage	Delivered Kelvin	Delivered Lumens	Delivered CRI	Code	Total Wattage	Delivered Kelvin	Delivered Lumens	Delivered CRI
IN3, IN6	Med	A-19 Medium 120V	L50	65	3000	8971 +90	L90	118	3000	16400 +90	
			L55	65	3500	8971 +90	L95	118	3500	16400 +90	
			L54	65	4000	8971 +90	L94	118	4000	16400 +90	
			L60	78	3000	10544 +90	L120	157	3000	21794 +90	
			L65	78	3500	10544 +90	L125	157	3500	21794 +90	
			L64	78	4000	10544 +90	L124	157	4000	21794 +90	

LED Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.