

CONE

Exterior Pendant






9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- LED Dimming:** Standard 1% 0-10V dimming.
- Listing:** ETL listed for wet locations.
- Canopy:** Matches fixture finish. Hanger 3 includes 10.125" dia by 2.625" H spinning.
- Driver:** Max remote driver installation distance 25ft from fixture body.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-5350- E- BLK- 1- A 038					
MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-5350 8lbs W 16" 3.6kg B 11" H 38"	A. 17LED30 B. 17LED35 C. 17LED40 D. 24LED30 E. 24LED35 F. 24LED40	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown	1. Stem Mount Remote Driver  Drivers mounted remotely 3. Stem Mount Oversized Canopy  Drivers mounted inside oversized canopy	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Specify overall height in inches.
GL-5351 10lbs W 24" 4.5kg B 15 3/8" H 42"	G. 15LED30 H. 15LED35 I. 15LED40 J. 26LED30 K. 26LED35 L. 26LED40 M. 39LED30 N. 39LED35 O. 39LED40	Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone			

All Dimensions are nominal.

Light Source Definition

Downlight Output						
Code	LED	Wattage	Lumens	Kelvin	CRI	
A	17LED30	17W	1534	3000	80	
B	17LED35	17W	1534	3500	80	
C	17LED40	17W	1534	4000	80	
D	24LED30	24W	2148	3000	80	
E	24LED35	24W	2148	3500	80	
F	24LED40	24W	2148	4000	80	
G	15LED30	15W	1361	3000	80	
H	15LED35	15W	1361	3500	80	
I	15LED40	15W	1361	4000	80	
J	26LED30	26W	2334	3000	80	
K	26LED35	26W	2334	3500	80	
L	26LED40	26W	2334	4000	80	
M	39LED30	39W	3501	3000	80	
N	39LED35	39W	3501	3500	80	
O	39LED40	39W	3501	4000	80	

Universal Voltage unless otherwise specified.
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

