

# CONE

## Interior Surface Mount




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- LED Dimming:** Standard 1% 0-10V dimming.
- Driver:** Integral in fixture body. Remote driver required for V,W,X lamping options.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Inner Finish:** Inner finish available in white, black, and gold liquid paint.
- Non-white inner finishes will reduce lumen output.
- Surge Protection:** External surge protector provided as standard.



### SAMPLE CATALOG NUMBER:

GL-3350-

MODEL NO.	E-	BLK-	MO-	A
MODEL NO.	LAMPING	OUTER FINISH	INNER FINISH	OPTIONS
<b>GL-3350</b> 8lbs W in 16" 3.6kg H in 11"	<b>A.</b> 17LED30 <b>B.</b> 17LED35 <b>C.</b> 17LED40 <b>D.</b> 24LED30 <b>E.</b> 24LED35 <b>F.</b> 24LED40	<b>Standard:</b> Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>WH</b> -White <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze <b>PG</b> -Pine Green <b>DO</b> -Deep Orange <b>PV</b> -Purple Violet <b>NB</b> -Navy Blue  Textured Powder <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBZ</b> -Textured Bronze <b>TST</b> -Stone	<b>Standard:</b> <b>MO</b> -Matches Outer Finish Liquid Paint <b>WH</b> -White <b>BLK</b> -Black <b>GL</b> -Gold	<b>A.</b> No Options <b>DM.</b> DMX Dimming Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
<b>GL-3351</b> 10lbs W in 24" 4.5kg H in 15 3/8"	<b>G.</b> 15LED30 <b>H.</b> 15LED35 <b>I.</b> 15LED40 <b>J.</b> 26LED30 <b>K.</b> 26LED35 <b>L.</b> 26LED40 <b>M.</b> 39LED30 <b>N.</b> 39LED35 <b>O.</b> 39LED40 <b>V.</b> 68LED30* <b>W.</b> 68LED35* <b>X.</b> 68LED40*			
	*Remote Driver only.	Outer finish designated by first finish code.	Inner finish designated by second finish code.	

All Dimensions are nominal.

### Light Source Definition

Downlight Output						Downlight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	17LED30	17W	1534	3000	80	V	1LED30	68W	5076*	3000	80
B	17LED35	17W	1534	3500	80	W	1LED35	68W	5076*	3500	80
C	17LED40	17W	1534	4000	80	X	1LED40	68W	5076*	4000	80
D	24LED30	24W	2148	3000	80						
E	24LED35	24W	2148	3500	80						
F	24LED40	24W	2148	4000	80						
G	15LED30	15W	1361	3000	80						
H	15LED35	15W	1361	3500	80						
I	15LED40	15W	1361	4000	80						
J	26LED30	26W	2334	3000	80						
K	26LED35	26W	2334	3500	80						
L	26LED40	26W	2334	4000	80						
M	39LED30	39W	3501	3000	80						
N	39LED35	39W	3501	3500	80						
O	39LED40	39W	3501	4000	80						

Universal Voltage unless otherwise specified.

Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

