

MEDI

Interior Pendant




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency 90CRI mid-power LEDs. Universal voltage.
- Uplight:** Optional uplight is wired on a second circuit. Standard satin white top lens.
- LED Dimming:** Standard 1% 0-10V dimming.
- Cable Hanger Option:** Standard 150" cable and white cord for on-site adjustability.
- Canopy:** Matches outer fixture finish. Hanger 3 & 4 with A-O lamping option includes 10.125" dia by 2.625" H spinning. V, W, X lamping includes 12" dia by 2" H.
- Driver:** Max remote driver installation distance 25ft from fixture body.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Inner Finish:** Inner finish matches outer finish.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:									
GL-2356-	E-	K-	BLK-	MO-	1-	A	038		
MODEL NO.	LAMPING	UPLIGHT	OUTER FINISH	INNER FINISH	HANGER	OPTIONS	OVERALL HEIGHT		
GL-2355 8lbs Win 16" 3.6kg B in 7 3/8" H in 38"	A. 26LED30 B. 26LED35 C. 26LED40 D. 26LED30 E. 26LED35 F. 26LED40 G. 39LED30 H. 39LED35 I. 39LED40 V. 68LED30* W. 68LED35* X. 68LED40*	NA. NONE J. 8UPLED30 K. 8UPLED35 L. 8UPLED40 M. 12UPLED30 N. 12UPLED35 O. 12UPLED40	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze PG- Pine Green DO- Deep Orange PV- Purple Violet NB- Navy Blue Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone	Standard: MO-Matches Outer Finish Liquid Paint WH- White BLK- Black GL- Gold	1. Stem Mount Remote Driver Drivers mounted remotely 2. Cable Mount Remote Driver Drivers mounted remotely 3. Stem Mount Oversized Canopy Drivers mounted inside oversized canopy 4. Cable Mount Oversized Canopy Drivers mounted inside oversized canopy	A. No Options BC. Black Cord Fixture supplied with black power cord. DM. DMX Dimming EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. Downlight only.	Specify overall height in inches for hanger styles 1 & 3.		
								GL-2356 10lbs Win 24" 4.5kg B in 11 9/16" H in 42"	
								GL-2357 15lbs Win 32" 6.8kg B in 15 11/16" H in 46"	
*Downlight only.							Outer finish designated by first finish code.	Inner finish designated by second finish code.	Hanger options 1&2 supplied with remote driver box.

All Dimensions are nominal.

Light Source Definition

Downlight Output						Uplight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	26LED30	15W	1538	3000	+90	J	8UPLED30	8W	866	3000	+90
B	26LED35	15W	1538	3500	+90	K	8UPLED35	8W	866	3500	+90
C	26LED40	15W	1538	4000	+90	L	8UPLED40	8W	866	4000	+90
D	26LED30	26W	2637	3000	+90	M	12UPLED30	12W	1213	3000	+90
E	26LED35	26W	2637	3500	+90	N	12UPLED35	12W	1213	3500	+90
F	26LED40	26W	2637	4000	+90	O	12UPLED40	12W	1213	4000	+90
G	39LED30	39W	3956	3000	+90						
H	39LED35	39W	3956	3500	+90						
I	39LED40	39W	3956	4000	+90						
V	68LED30	68W	6009*	3000	+90						
W	68LED35	68W	6009*	3500	+90						
X	68LED40	68W	6009*	4000	+90						

*Projected

Universal Voltage unless otherwise specified.
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

