

MEDI

Exterior Surface Mount




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- LED Dimming:** Standard 1% 0-10V dimming.
- Listing:** ETL listed for wet locations.
- Driver:** Integral in fixture body.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-9356-			
MODEL NO.	E-	BLK-	A
MODEL NO.	LAMPING	FINISH	OPTIONS
GL-9355 8lbs Win 16" 3.6kg H in 7 3/8"	A. 15LED30 B. 15LED35 C. 15LED40 D. 26LED30 E. 26LED35 F. 26LED40 G. 39LED30 H. 39LED35 I. 39LED40	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze PG- Pine Green DO- Deep Orange PV- Purple Violet NB- Navy Blue Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-9356 10lbs Win 24" 4.5kg H in 11 9/16"			
GL-9357 15lbs Win 32" 6.8kg H in 15 11/16"			

All Dimensions are nominal.

Light Source Definition

Downlight Output						
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	
A	15LED30	15W	1538	3000	80	
B	15LED35	15W	1538	3500	80	
C	15LED40	15W	1538	4000	80	
D	26LED30	26W	2637	3000	80	
E	26LED35	26W	2637	3500	80	
F	26LED40	26W	2637	4000	80	
G	39LED30	39W	3956	3000	80	
H	39LED35	39W	3956	3500	80	
I	39LED40	39W	3956	4000	80	

Universal Voltage unless otherwise specified.
Fixture tested with white finish. Non-white finishes will reduce lumen output.

