

# MEDI

## Interior Surface Mount




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- LED Dimming:** Standard 1% 0-10V dimming.
- Driver:** Integral in fixture body. Remote driver required for V,W,X lamping options.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Inner Finish:** Inner finish available in white, black, and gold liquid paint. Non-white inner finishes will reduce lumen output.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-3356-				
MODEL NO.	E-	BLK-	MO-	A
MODEL NO.	LAMPING	OUTER FINISH	INNER FINISH	OPTIONS
<b>GL-3355</b> 8lbs Win 16" 3.6kg H in 7 3/8"	<b>A.</b> 15LED30 <b>B.</b> 15LED35 <b>C.</b> 15LED40 <b>D.</b> 26LED30 <b>E.</b> 26LED35 <b>F.</b> 26LED40 <b>G.</b> 39LED30 <b>H.</b> 39LED35 <b>I.</b> 39LED40 <b>V.</b> 68LED30* <b>W.</b> 68LED35* <b>X.</b> 68LED40*	<b>Standard:</b> Powder Coat <b>BLK-</b> Black <b>BL-</b> Blue <b>GR-</b> Gray <b>LG-</b> Light Gray <b>BE-</b> Beige <b>PAB-</b> Antique Brass <b>PA-</b> Painted Aluminum <b>PTC-</b> Painted Copper <b>WH-</b> White <b>DBZ-</b> Dark Bronze <b>NSN-</b> New Satin Nickel <b>BRN-</b> Brown <b>RD-</b> Red <b>CH-</b> Champagne <b>RG-</b> Reed Green <b>SG-</b> Sungold <b>GM-</b> Gun Metal <b>POR-</b> Oil Rubbed Bronze <b>PG-</b> Pine Green <b>DO-</b> Deep Orange <b>PV-</b> Purple Violet <b>NB-</b> Navy Blue  <b>Textured Powder</b> <b>TLV-</b> Light Verdigris <b>TWH-</b> Textured White <b>TBL-</b> Textured Black <b>TS-</b> Textured Silver <b>TBZ-</b> Textured Bronze <b>TST-</b> Stone	<b>Standard:</b> MO-Matches Outer Finish Liquid Paint <b>WH-</b> White <b>BLK-</b> Black <b>GL-</b> Gold	<b>A.</b> No Options  <b>DM.</b> DMX Dimming Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F.  <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
<b>GL-3356</b> 10lbs Win 24" 4.5kg H in 11 9/16"				
<b>GL-3357</b> 15lbs Win 32" 6.8kg H in 15 11/16"				
	*Remote Driver only.	Outer finish designated by first finish code.	Inner finish designated by second finish code.	

All Dimensions are nominal.

### Light Source Definition

Downlight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	15LED30	15W	1538	3000	80
B	15LED35	15W	1538	3500	80
C	15LED40	15W	1538	4000	80
D	26LED30	26W	2637	3000	80
E	26LED35	26W	2637	3500	80
F	26LED40	26W	2637	4000	80
G	39LED30	39W	3956	3000	80
H	39LED35	39W	3956	3500	80
I	39LED40	39W	3956	4000	80
V	68LED30	68W	6009*	3000	80
W	68LED35	68W	6009*	3500	80
X	68LED40	68W	6009*	4000	80

\*Projected

Universal Voltage unless otherwise specified.  
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.