

MARINA TUNABLE WHITE

Interior Round Semi-Surface Mount



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

Tunable White: LED option (TW) features tunable white technology that adjusts from 6500K-2700K. For proper control, fixture needs two 0-10V dimming controls.

LED Tuning: CCT tunable using 0-10V wall control. TRIAC, DALI, or DMX available upon request.

LED Dimming: Intensity adjustable using 1% 0-10V wall control. TRIAC, DALI, or DMX available upon request.

Shade: Standard fabric shade with removable white acrylic diffuser. Custom shapes, sizes, and colors available.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.

Standard textured white finish



SAMPLE CATALOG NUMBER: GL-3751-				TW5-	W-	A
MODEL NO.				LAMPING	SHADE	OPTIONS
GL-3751	W in 24"	mm 610		TW5	W White	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.
15lbs	D in 11.5"	mm 295			C Cream	
7kg					BL Blue	
					BK Black	
GL-3752	W in 30"	mm 760		TW5	S Stone	Washable: WW White WC Cream WLG Lt Gray WGR Gray WBK Black WR Red WBL Blue
18lbs	D in 12.5"	mm 320			R Red	
8kg						
GL-3753	W in 36"	mm 915		TW8		Shade options may vary based on availability. Consult Finish Guide at glighting.com for current options.
20lbs	D in 13.5"	mm 340				
9kg						
GL-3754	W in 48"	mm 1220		TW8		
25lbs	D in 15.5"	mm 395				
11.5kg						

All Dimensions are nominal.

Shade

<u>Standard</u>						
White	Cream	Blue	Stone	Red	Black	
<u>Washable - Trilam</u>						
White	Cream	Light Gray	Gray	Black	Red	Blue

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
TW5	72	7736	3500-1800
TW8	114	12248	3500-1800

Universal Voltage unless otherwise specified.