

SONOMA

Interior Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency +90CRI mid-power LEDs are field serviceable.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.

Shade: Standard fabric shade with removable white acrylic diffuser. Custom shapes, sizes, and colors available.


Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.

Cable Hanger Option: Supplied with standard 72" white cord and cable. Field adjustable.

Finish: Highly durable oven cured no VOC premium powder coat.

Modifications: Consult factory for lamping or cluster options.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2901-	L55-	W-	NSN-	1-	A-	045
MODEL NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-2901 W in 30 1/8" 15lbs B in 34" 7kg H in 45"	L50. 5LED30 L55. 5LED35 L54. 5LED40 IN4. 4MED*	W White C Cream BL Blue BK Black S Stone R Red Washable: WW White WC Cream WLG Lt Gray WGR Gray WBK Black WR Red WBL Blue Shade options may vary based on availability. Consult Finish Guide at glighting.com for current options.	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone	1. Stem Mount Drivers mounted integrally 2. Cable Mount Drivers mounted integrally	A. No Options BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Standard 45" overall height. Available up to 93". For custom overall height, contact factory.

All Dimensions are nominal. 120V only*

Shade

Standard



White



Cream



Blue



Stone



Red



Black

Washable - Trilam



White



Cream



Light Gray



Gray



Black



Red



Blue

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Total Wattage	Board Lumens	Kelvin	CRI	Code	Lamp	Lamp Base
L50	65W	9750	3000	+90	IN4	A-19	Medium
L55	65W	9750	3500	+90			
L54	65W	9750	4000	+90			

Universal Voltage unless otherwise specified.