

TAHOE WARM DIM

Interior Square Semi-Surface Mount



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

Warm Dim: LED option (WD) features warm dimming technology that dims smoothly from 3500K-1800K with standard 1% 0-10V dimming.


LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.

Shade: Standard fabric shade with removable white acrylic diffuser. Custom shapes, sizes, and colors available.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.

Standard textured white finish



SAMPLE CATALOG NUMBER: GL-3757-				WD5-	W-	A
MODEL NO.				LAMPING	SHADE	OPTIONS
GL-3757	W in 24"	mm 610		WD5	W White	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.
15lbs	D in 11.5"	mm 295			C Cream	
7kg					BL Blue	
					BK Black	
GL-3758	W in 30"	mm 760		WD5	S Stone	
18lbs	D in 12.5"	mm 320			R Red	
8kg						
GL-3759	W in 36"	mm 915		WD8	Washable:	
20lbs	D in 13.5"	mm 340			WW White	
9kg					WC Cream	
					WLG Lt Gray	
GL-3760	W in 48"	mm 1220		WD8	WGR Gray	
25lbs	D in 15.5"	mm 395			WBK Black	
11.5kg					WR Red	
					WBL Blue	

All Dimensions are nominal.

Shade

Standard						
White	Cream	Blue	Stone	Red	Black	
Washable - Trilam						
White	Cream	Light Gray	Gray	Black	Red	Blue

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
WD5	107	7736	3500-1800
WD8	170	12248	3500-1800

Universal Voltage unless otherwise specified.