

TAHOE

Interior Square Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.

Lower Output: Lamping code ending with LO features lower lumen output.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.

Shade: Standard fabric shade with removable white acrylic diffuser.

Custom shapes, sizes, and colors available.


Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.

Cable Hanger Option: Supplied with standard 72" white cord and cable. Field adjustable.

Finish: Highly durable oven cured no VOC premium powder coat.

Modifications: Consult factory for lamping or cluster options.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2757-		L55-	W-	NSN-	1-	A- 023
MODEL NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-2755 W in 14" 5lbs D in 9.5" 2.25kg H in 21"	L10. 1LED30 LL10. 1LED30LO L15. 1LED35 LL15. 1LED35LO L14. 1LED40 LL14. 1LED40LO IN3. 3MED	W White C Cream BL Blue BK Black S Stone R Red	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	1. Stem 5. Cord & Cable Supplied with white cord with hanger option 5.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.
GL-2756 W in 18" 5lbs D in 9.5" 2.25kg H in 21"	L10. 1LED30 LL10. 1LED30LO L15. 1LED35 LL15. 1LED35LO L14. 1LED40 LL14. 1LED40LO IN3. 3MED	BK Black S Stone R Red				
GL-2757 W in 24" 15lbs D in 11.5" 7kg H in 23"	L50. 5LED30 LL50. 5LED30LO L55. 5LED35 LL55. 5LED35LO L54. 5LED40 LL54. 5LED40LO IN3. 3MED	Washable: WW White WC Cream WLG Lt Gray WGR Gray WBK Black WR Red WBL Blue				
GL-2758 W in 30" 18lbs D in 12.5" 8kg H in 23"	L50. 5LED30 LL50. 5LED30LO L55. 5LED35 LL55. 5LED35LO L54. 5LED40 LL54. 5LED40LO IN3. 3MED					
GL-2759 W in 36" 20lbs D in 13.5" 9kg H in 25"	L80. 8LED30 LL80. 8LED30LO L85. 8LED35 LL85. 8LED35LO L84. 8LED40 LL84. 8LED40LO IN6. 6MED					
GL-2760 W in 48" 25lbs D in 15.5" 11.5kg H in 27"	L80. 8LED30 LL80. 8LED30LO L85. 8LED35 LL85. 8LED35LO L84. 8LED40 LL84. 8LED40LO IN6. 6MED	Shade options may vary based on availability. Consult Finish Guide at glighting.com for current options.				

All Dimensions are nominal.

Shade

<u>Standard</u>						
	White		Cream		Blue	
	Red		Black			
<u>Washable - Trilam</u>						
	White		Cream		Light Gray	
	Black		Red		Blue	

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Lamp	Type	Lamp Base	Code	Lamp	Total Wattage	Delivered Lumens	Kelvin	CRI
IN3,IN6	MED	A-19	Medium 120V	LL50	5LED30LO	39W	4462	3000	+90
				LL55	5LED35LO	39W	4462	3500	+90
				LL54	5LED40LO	39W	4462	4000	+90
				L50	5LED30	65W	7436	3000	+90
				L55	5LED35	65W	7436	3500	+90
				L54	5LED40	65W	7436	4000	+90
				LL80	8LED30LO	63W	7126	3000	+90
				LL85	8LED35LO	63W	7126	3500	+90
				LL84	8LED40LO	63W	7126	4000	+90
				L80	8LED30	105W	12248	3000	+90
				L85	8LED35	105W	12248	3500	+90
				L84	8LED40	105W	12248	4000	+90

Universal Voltage unless otherwise specified.

Contact factory for availability of other lamp configurations.