

MEDI

Exterior Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.

LED Dimming: Standard 1% 0-10V dimming.

Listing: ETL listed for wet locations.


Canopy: Matches fixture finish. Hanger 3 includes 10.125" dia by 2.625" H spinning.

Driver: Max remote driver installation distance 25ft from fixture body.

Acrylic: Acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:					
GL-5356-		E-	BLK-	1-	A 038
MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-5355 8lbs Win 16" 3.6kg B in 7 3/8" H in 38"	A. 15LED30 B. 15LED35 C. 15LED40 D. 26LED30 E. 26LED35 F. 26LED40 G. 39LED30 H. 39LED35 I. 39LED40	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	1. Stem Mount Remote Driver  Drivers mounted remotely 3. Stem Mount Oversized Canopy  Drivers mounted inside oversized canopy	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Specify overall height in inches.
GL-5356 10lbs Win 24" 4.5kg B in 11 9/16" H in 42"					
GL-5357 15lbs Win 32" 6.8kg B in 15 11/16" H in 46"					
GL-5358 78lbs Win 60" 35kg B in 31" H in 50"					

All Dimensions are nominal.

Light Source Definition

Downlight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	15LED30	15W	1538	3000	80
B	15LED35	15W	1538	3500	80
C	15LED40	15W	1538	4000	80
D	26LED30	26W	2637	3000	80
E	26LED35	26W	2637	3500	80
F	26LED40	26W	2637	4000	80
G	39LED30	39W	3956	3000	80
H	39LED35	39W	3956	3500	80
I	39LED40	39W	3956	4000	80

Universal Voltage unless otherwise specified.
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.