

MEDI

Interior Surface Mount



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.

LED Dimming: Standard 1% 0-10V dimming.

Driver: Integral in fixture body. Remote driver required for V,W,X lamping options.


Acrylic: Acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat.

Inner Finish: Inner finish available in white, black, and gold liquid paint.

Non-white inner finishes will reduce lumen output.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-3356-				
MODEL NO.	LAMPING	OUTER FINISH	INNER FINISH	OPTIONS
GL-3355 8lbs Win 16" 3.6kg H in 7 3/8"	A. 15LED30 B. 15LED35 C. 15LED40 D. 26LED30 E. 26LED35 F. 26LED40 G. 39LED30 H. 39LED35 I. 39LED40 V. 68LED30* W. 68LED35* X. 68LED40*	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone	Standard: MO -Matches Outer Finish Liquid Paint WH -White BLK -Black GL -Gold SL -Silver CP -Copper	A. No Options DM. DMX Dimming Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-3356 10lbs Win 24" 4.5kg H in 11 9/16"				
GL-3357 15lbs Win 32" 6.8kg H in 15 11/16"				
GL-3358 78lbs Win 60" 35kg H in 28"				
	*Remote Driver only.	Outer finish designated by first finish code.	Inner finish designated by second finish code.	

All Dimensions are nominal.

Light Source Definition

Downlight Output						
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	
A	15LED30	15W	1538	3000	80	
B	15LED35	15W	1538	3500	80	
C	15LED40	15W	1538	4000	80	
D	26LED30	26W	2637	3000	80	
E	26LED35	26W	2637	3500	80	
F	26LED40	26W	2637	4000	80	
G	39LED30	39W	3956	3000	80	
H	39LED35	39W	3956	3500	80	
I	39LED40	39W	3956	4000	80	
V	68LED30	68W	6009*	3000	80	
W	68LED35	68W	6009*	3500	80	
X	68LED40	68W	6009*	4000	80	

*Projected

Universal Voltage unless otherwise specified.
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.