

GENERAL SPECIFICATION

LED: High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.


Acrylic: Satin white seamless acrylic is UL-94 HB Flame Class rated.

Cable Hanger: Comes with 72" cable and cord for on-site adjustability.

Canopy: Matches fixture finish.

Finish: Highly durable oven cured no VOC premium powder coat.
Spinning interior White Liquid Paint.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-2641-					E-	PTC-	1-	A
MODEL NO.					LAMPING	FINISH	HANGER	OPTIONS
GL-2640	W 26" in	660 mm			A. 4LED30	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone	1. Cable 	A. No Options BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32"-131°F. Specify 120 or 277 voltage.
	10lbs B 7 1/2" in	190 mm			B. 4LED35			
	4.5kg H 20"-68" in	510-1730 mm			C. 4LED40			
GL-2641	W 37" in	940 mm			D. 5LED30	Not available in standard white finish		
	15lbs B 7 1/2" in	190 mm			E. 5LED35			
	6.8kg H 20"-68" in	510-1730 mm			F. 5LED40			

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	Rated Life Hrs	Delivered Lumens	Kelvin	CRI
4LED30	52W	50000	4310	3000	+90
4LED35	52W	50000	4310	3500	+90
4LED40	52W	50000	4310	4000	+90
5LED30	65W	50000	5320	3000	+90
5LED35	65W	50000	5320	3500	+90
5LED40	65W	50000	5320	4000	+90

Universal Voltage unless otherwise specified.

Contact factory for availability of other lamp configurations.