

# OCULUS RGB+W

## Interior Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**RGB+White:** LED option (RGB30, RGB35, & RGB40) features a full power white and RGB color changing light source. A second circuit controls the white channel. RGB channel wired DMX ready, full white 1% 0-10V dimming standard.

**RGB:** LED option features RGB color changing light source. RGB channel wired DMX ready.

**Static Color:** LED options (Red, Green, or Blue) feature static color.

**Acrylic:** Satin white seamless acrylic is UL-94 HB Flame Class rated.


**Cable Hanger:** Comes with 72" cable and cord for on-site adjustability.

**Canopy:** Matches fixture finish.

**Finish:** Highly durable oven cured no VOC premium powder coat. Spinning interior White Liquid Paint.

**DMX:** Controls by others.

**Surge Protection:** External surge protector provided as standard.



| SAMPLE CATALOG NUMBER:<br>GL-2641-                                                           |                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                     |                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MODEL NO.                                                                                    | S-<br>LAMPING                                                                                                                    | PTC-<br>FINISH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 1-<br>HANGER        | A<br>OPTIONS                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>GL-2640</b> W in 26" mm 660<br>10lbs B in 7 1/2" mm 190<br>4.5kg H in 20"-68" mm 510-1730 | <b>G. RED</b><br><b>H. GREEN</b><br><b>I. BLUE</b><br><b>J. RGB*</b><br><b>K. RGB30*</b><br><b>L. RGB35*</b><br><b>M. RGB40*</b> | <b>Standard:</b><br><b>BLK-Black</b><br><b>BL-Blue</b><br><b>GR-Gray</b><br><b>LG-Light Gray</b><br><b>BE-Beige</b><br><b>PAB-Antique Brass</b><br><b>PA-Painted Aluminum</b><br><b>PTC-Painted Copper</b><br><b>DBZ-Dark Bronze</b><br><b>NSN-New Satin Nickel</b><br><b>BRN-Brown</b><br><b>RD-Red</b><br><b>CH-Champagne</b><br><b>RG-Reed Green</b><br><b>SG-Sungold</b><br><b>GM-Gun Metal</b><br><b>POR-Oil Rubbed Bronze</b><br><b>PG-Pine Green</b><br><b>DO-Deep Orange</b><br><b>PV-Purple Violet</b><br><b>NB-Navy Blue</b><br><b>Textured Powder</b><br><b>TLV-Light Verdigris</b><br><b>TWH-Textured White</b><br><b>TBL-Textured Black</b><br><b>TS-Textured Silver</b><br><b>TBZ-Textured Bronze</b><br><b>TST-Stone</b> | <b>1. Cable</b><br> | <b>A. No Options</b><br><b>BC. Black Cord</b><br>Fixture supplied with black power cord.<br><b>LC. 150" Cord &amp; Cable</b><br>Fixture supplied with 150" of cable and standard white cord or optional black cord.<br><b>EL. Emergency LED</b><br>Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. |
| <b>GL-2641</b> W in 37" mm 940<br>15lbs B in 7 1/2" mm 190<br>6.8kg H in 20"-68" mm 510-1730 | <b>N. RED</b><br><b>O. GREEN</b><br><b>P. BLUE</b><br><b>Q. RGB*</b><br><b>R. RGB30*</b><br><b>S. RGB35*</b><br><b>T. RGB40*</b> | <b>Not available in standard white finish</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                     |                                                                                                                                                                                                                                                                                                                                                                                                |

All Dimensions are nominal.  
 \*DMX controls supplied by others

### Light Source Definition

| Fixture | Total<br>Wattage | CRI | Rated<br>Life Hrs | Delivered<br>Lumens |
|---------|------------------|-----|-------------------|---------------------|
| GL-2640 | 57W              | +80 | 50000             | 4310                |
| GL-2641 | 72W              | +80 | 50000             | 5320                |

Universal Voltage unless otherwise specified.