OCULUS

Interior Surface Mount

G Lighting
9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000
sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.
LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.
Acrylic: Satin white seamless acrylic is UL-94 HB Flame Class rated.
Finish: Highly durable oven cured no VOC premium powder coat.
Spinning interior White Liquid Paint.
Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:
GL-3641- E- NSN- A

MODEL NO.	LAMPING	FINISH	OPTIONS
GL-3640 W 26" in 660 mm 8lbs B 7 1/2" in 190 mm 3.5kg	**A.** 4LED30 **B.** 4LED35 **C.** 4LED40	Standard: Powder Coat **BLK**-Black **BL**-Blue **GR**-Gray **LG**-Light Gray **BE**-Beige **PAB**-Antique Brass **PA**-Painted Aluminum **PTC**-Painted Copper **DBZ**-Dark Bronze **NSN**-New Satin Nickel **BRN**-Brown **RD**-Red **CH**-Champagne **RG**-Reed Green **SG**-Sungold **GM**-Gun Metal **POR**-Oil Rubbed Bronze **PG**-Pine Green **DO**-Deep Orange **PV**-Purple Violet **NB**-Navy Blue Textured Powder **TLV**-Light Verdigris **TWH**-Textured White **TBL**-Textured Black **TS**-Textured Silver **TBZ**-Textured Bronze **TST**-Stone **Not available in standard white finish**	**A.** No Options **EL.** Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-3641 W 37" in 940 mm 10lbs B 7 1/2" in 190 mm 4.5kg	**D.** 5LED30 **E.** 5LED35 **F.** 5LED40		

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	Rated Life Hrs	Delivered Lumens	Kelvin	CRI
4LED30	52W	50000	4310	3000	+90
4LED35	52W	50000	4310	3500	+90
4LED40	52W	50000	4310	4000	+90
5LED30	65W	50000	5320	3000	+90
5LED35	65W	50000	5320	3500	+90
5LED40	65W	50000	5320	4000	+90

Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.

© Gross Chandelier Co.
G Lighting reserves the right to modify existing designs to improve appearance or function
G Lighting products are union made.