ADAGIO

Indoor Surface Mount

G Lighting
9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000
sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.
LED Dimming: Standard 1% 0-10V dimming with LED lamping option.
Body: GL-3000-3003 ring spun in 18ga steel or .050 aluminum.
Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.
Finish: Highly durable oven cured no VOC premium powder coat.
Surge Protection: External surge protector provided as standard.





SAMPLE CATALOG NUMBER:
GL-3002- L45- S- NSN- A

MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)
GL-3000 10 lbs 5 kg B in 18" mm 457 W in 23 1/4" mm 686 D in 7 5/8" mm 229	**IN3.** 3MED **L30.** 3LED30 **L35.** 3LED35 **L34.** 3LED40	Standard: **S.** Satin White Optional: **W.** White Opal Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat **BLK**-Black **BL**-Blue **GR**-Gray **LG**-Light Gray **BE**-Beige **PAB**-Antique Brass **PA**-Painted Aluminum **PTC**-Painted Copper **WH**-White **DBZ**-Dark Bronze **NSN**-New Satin Nickel **BRN**-Brown **RD**-Red **CH**-Champagne **RG**-Reed Green **SG**-Sungold **GM**-Gun Metal **POR**-Oil Rubbed Bronze **PG**-Pine Green **DO**-Deep Orange **PV**-Purple Violet **NB**-Navy Blue Textured Powder **TLV**-Light Verdigris **TWH**-Textured White **TBL**-Textured Black **TS**-Textured Silver **TBZ**-Textured Bronze **TST**-Stone	**A.** No Options **F1.** Add Finial  **F2.** Add Finial  **B.** Damp Location Available in powder coat or Satin Aluminum finish. **EL.** Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. Multi-circuiting available upon request.
GL-3001 17 lbs 8 kg B in 24" mm 610 W in 30 5/8" mm 780 D in 9" mm 230	**IN3.** 3MED **L40.** 4LED30 **L45.** 4LED35 **L44.** 4LED40			
GL-3002 22 lbs 10 kg B in 30" mm 762 W in 36 1/4" mm 1016 D in 9 7/8" mm 270	**IN6.** 6MED **L40.** 4LED30 **L45.** 4LED35 **L44.** 4LED40 **L60.** 6LED30 **L65.** 6LED35 **L64.** 6LED40			
GL-3003 33 lbs 15 kg B in 38" mm 965 W in 44 7/8" mm 1194 D in 11 5/8" mm 311	**IN6.** 6MED **L60.** 6LED30 **L65.** 6LED35 **L64.** 6LED40 **L80.** 8LED30 **L85.** 8LED35 **L84.** 8LED40			

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Lamp Definition

Code	Lamp	Type	Lamp Base
IN3, IN6	Med	A-19	Medium 120V

Code	Total Wattage	Kelvin	Delivered Lumens	CRI
L30	39	3000	4211	+90
L35	39	3500	4211	+90
L34	39	4000	4211	+90
L40	52	3000	5074	+90
L45	52	3500	5074	+90
L44	52	4000	5074	+90
L60	78	3000	8063	+90
L65	78	3500	8063	+90
L64	78	4000	8063	+90
L80	105	3000	12035	+90
L85	105	3500	12035	+90
L84	105	4000	12035	+90

Contact factory for availability of other lamp configurations.
Universal Voltage unless otherwise specified.

© Gross Chandelier Co.
G Lighting reserves the right to modify existing designs to improve appearance or function
G Lighting products are union made.