
DEMI

Exterior Pendant

G Lighting
9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000
sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.
LED Dimming: Standard 1% 0-10V dimming.
Listing: ETL listed for wet locations.
Canopy: Matches fixture finish. Hanger 3 includes 10.125“ dia by 2.625” H spinning.
Driver: Max remote driver installation distance 25ft from fixture body.
Acrylic: Acrylic is UL-94 HB Flame Class rated.
Finish: Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.
Surge Protection: External surge protector provided as standard.





SAMPLE CATALOG NUMBER:
GL-5360- E- BLK- 1- A 030

MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-5360 10lbs W 24” 4.5kg B 6” H 30”	**A.** 15LED30 **B.** 15LED35 **C.** 15LED40 **D.** 26LED30 **E.** 26LED35 **F.** 26LED40 **G.** 39LED30 **H.** 39LED35 **I.** 39LED40	Standard: Powder Coat **BLK**-Black **BL**-Blue **GR**-Gray **LG**-Light Gray **BE**-Beige **PAB**-Antique Brass **PA**-Painted Aluminum **PTC**-Painted Copper **WH**-White **DBZ**-Dark Bronze **NSN**-New Satin Nickel **BRN**-Brown **RD**-Red **CH**-Champagne **RG**-Reed Green **SG**-Sungold **GM**-Gun Metal **POR**-Oil Rubbed Bronze **PG**-Pine Green **DO**-Deep Orange **PV**-Purple Violet **NB**-Navy Blue Textured Powder **TLV**-Light Verdigris **TWH**-Textured White **TBL**-Textured Black **TS**-Textured Silver **TBZ**-Textured Bronze **TST**-Stone	**1.** Rigid Stem Mount Remote Driver  Drivers mounted remotely **3.** Rigid Stem Mount Oversized Canopy  Drivers mounted inside oversized canopy Tie offs factory recommended. Supplied by others.	**A.** No Options **EL.** Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Specify overal height in inches For stem lengths longer than 24”, consult factory.
GL-5361 10lbs W 30” 4.5kg B 7 7/16” H 32”					
GL-5362 15lbs W 48” 7kg B 12” H 36”					

All Dimensions are nominal.

Light Source Definition

Downlight Output

Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	15LED30	15W	1695	3000	80
B	15LED35	15W	1695	3500	80
C	15LED40	15W	1695	4000	80
D	26LED30	26W	2906	3000	80
E	26LED35	26W	2906	3500	80
F	26LED40	26W	2906	4000	80
G	39LED30	39W	4359	3000	80
H	39LED35	39W	4359	3500	80
I	39LED40	39W	4359	4000	80

Universal Voltage unless otherwise specified.
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

© Gross Chandelier Co.
G Lighting reserves the right to modify existing designs to improve appearance or function
G Lighting products are union made.