ECLIPSE

Indoor Pendant

G Lighting
9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000
sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.

LED Dimming: Standard 1% 0-10V dimming with LED lamping option.


Body: Ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.

Canopy: Low profile. May be mounted on flat or sloped ceilings up to 40°.

Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.





SAMPLE CATALOG NUMBER:

GL-2162-	L95-	S-	NSN-	1-	A-	038

MODEL NO.

GL-2160

14lbs	B	in	18”	mm	457
6 kg	W	in	23”	mm	585
	D	in	7 1/2”	mm	190
	H	in	29”	mm	737

GL-2161

21lbs	B	in	24”	mm	610
10 kg	W	in	29”	mm	735
	D	in	8 1/2”	mm	215
	H	in	34”	mm	865

GL-2162

29lbs	B	in	30”	mm	762
13kg	W	in	35”	mm	890
	D	in	9 1/2”	mm	240
	H	in	38”	mm	965

GL-2163

37lbs	B	in	38”	mm	965
17kg	W	in	43”	mm	1090
	D	in	11”	mm	280
	H	in	42”	mm	1070

LAMPING

IN3. 3MED — **L50.** 5LED30, **L55.** 5LED35, **L54.** 5LED40

IN3. 3MED — **L60.** 6LED30, **L65.** 6LED35, **L64.** 6LED40

IN6. 6MED — **L90.** 9LED30, **L95.** 9LED35, **L94.** 9LED40

IN6. 6MED — **L120.** 12LED30, **L125.** 12LED35, **L124.** 12LED40

ACRYLIC

Standard:

S. Satin White

Optional:

W. White Opal

Acrylic is UL-94 HB Flame Class rated.

FINISH

Standard:

Powder Coat

BLK-Black
BL-Blue
GR-Gray
LG-Light Gray
BE-Beige
PAB-Antique Brass
PA-Painted Aluminum
PTC-Painted Copper
WH-White
DBZ-Dark Bronze
NSN-New Satin Nickel
BRN-Brown
RD-Red
CH-Champagne
RG-Reed Green
SG-Sungold
GM-Gun Metal
POR-Oil Rubbed Bronze
PG-Pine Green
DO-Deep Orange
PV-Purple Violet
NB-Navy Blue

Textured Powder

TLV-Light Verdigris
TWH-Textured White
TBL-Textured Black
TS-Textured Silver
TBZ-Textured Bronze
TST-Stone

HANGER

1. Stem



2. Cable



3. Arms



4. Stem Cluster



Custom lengths available. For heights longer than standard, additional length will be added to top stem.

OPTION(S)

A. No Options

F1. Add Finial



F2. Add Finial



B. Damp Location
Available in powder coat or Satin Aluminum finish.

EL. Emergency LED
Remote mount up to 10’ from lamping in controlled environment with an area temperature range of 32°-131°F. LED only.

W. White Opal Top Lens
INC only

C. Clear Top Lens
INC only

P. Perforated Top Lens
INC only

Multi-circuiting available upon request.

OVERALL HEIGHT

Standard overall height shown by model no.

For custom overall height, specify in inches.

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Lamp Definition

Code	Lamp	Type	Lamp Base
IN3, IN6	Med	A-19	Medium 120V

Code	Total Wattage	Kelvin	Delivered Lumens	CRI
L50	65	3000	8971	+90
L55	65	3500	8971	+90
L54	65	4000	8971	+90

Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.

Code	Total Wattage	Kelvin	Delivered Lumens	CRI
L60	78	3000	10544	+90
L65	78	3500	10544	+90
L64	78	4000	10544	+90
L90	118	3000	16400	+90
L95	118	3500	16400	+90
L94	118	4000	16400	+90
L120	157	3000	21794	+90
L125	157	3500	21794	+90
L124	157	4000	21794	+90

© Gross Chandelier Co.

G Lighting reserves the right to modify existing designs to improve appearance or function

G Lighting products are union made.