
ODYSSEY

Exterior Pendant

G Lighting
9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000
sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.
LED Dimming: Standard 1% 0-10V dimming.
Listing: ETL listed for wet locations.
Canopy: Matches fixture finish. Hanger 3 includes 10.125“ dia by 2.625” H spinning.
Driver: Max remote driver installation distance 25ft from fixture body.
Acrylic: Acrylic is UL-94 HB Flame Class rated.
Finish: Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.
Surge Protection: External surge protector provided as standard.





SAMPLE CATALOG NUMBER:

GL-5380-	E-	BLK-	1-	A	034
MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS	OVERALL HEIGHT

GL-5380 W 19 5/8”
8lbs B 10”
3.6kg H 34”

A. 15LED30
B. 15LED35
C. 15LED40
D. 26LED30
E. 26LED35
F. 26LED40
G. 39LED30
H. 39LED35
I. 39LED40

Standard:

Powder Coat
BLK-Black
BL-Blue
GR-Gray
LG-Light Gray
BE-Beige
PAB-Antique Brass
PA-Painted Aluminum
PTC-Painted Copper
WH-White
DBZ-Dark Bronze
NSN-New Satin Nickel
BRN-Brown
RD-Red
CH-Champagne
RG-Reed Green
SG-Sungold
GM-Gun Metal
POR-Oil Rubbed Bronze
PG-Pine Green
DO-Deep Orange
PV-Purple Violet
NB-Navy Blue

Textured Powder
TLV-Light Verdigris
TWH-Textured White
TBL-Textured Black
TS-Textured Silver
TBZ-Textured Bronze
TST-Stone

1. Rigid Stem Mount Remote Driver



Drivers mounted remotely

3. Rigid Stem Mount Oversized Canopy



Drivers mounted inside oversized canopy

Tie offs factory recommended. Supplied by others.

A. No Options

EL. Emergency LED
Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage

Specify overal height in inches for hanger styles 1 & 3.

For stem lengths longer than 24”, consult factory.

All Dimensions are nominal.

Light Source Definition

Downlight Output

Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	15LED30	15W	1538	3000	80
B	15LED35	15W	1538	3500	80
C	15LED40	15W	1538	4000	80
D	26LED30	26W	2637	3000	80
E	26LED35	26W	2637	3500	80
F	26LED40	26W	2637	4000	80
G	39LED30	39W	3956	3000	80
H	39LED35	39W	3956	3500	80
I	39LED40	39W	3956	4000	80

Universal Voltage unless otherwise specified.
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

© Gross Chandelier Co.

G Lighting reserves the right to modify existing designs to improve appearance or function

G Lighting products are union made.