PLYMOUTH

Indoor Pendant

G Lighting
9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000
sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.

LED Dimming: Standard 1% 0-10V dimming with LED lamping option.

Body: GL-2170-2173 ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.

Canopy: Low profile. May be mounted on flat or sloped ceilings up to 40°.

Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



Textured white pan with LED lamping



SAMPLE CATALOG NUMBER:

GL-2172- | L95- | S- | NSN- | 1- | A- | 038

MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
GL-2170 14lbs B in 18" mm 460 6 kg W in 24" mm 610 D in 6" mm 150 H in 29" mm 740	**IN3.** 3MED **L50.** 5LED30 **L55.** 5LED35 **L54.** 5LED40	Standard: **S.** Satin White Optional: **W.** White Opal Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat **BLK**-Black **BL**-Blue **GR**-Gray **LG**-Light Gray **BE**-Beige **PAB**-Antique Brass **PA**-Painted Aluminum **PTC**-Painted Copper **WH**-White **DBZ**-Dark Bronze **NSN**-New Satin Nickel **BRN**-Brown **RD**-Red **CH**-Champagne **PG**-Pine Green **DO**-Deep Orange **PV**-Purple Violet **NB**-Navy Blue Textured Powder **TLV**-Light Verdigris **TWH**-Textured White **TBL**-Textured Black **TS**-Textured Silver **TBZ**-Textured Bronze **TST**-Stone	**1.** Stem **2.** Cable **3.** Arms **4.** Stem Cluster Custom lengths available. For heights longer than standard, additional length will be added to top stem.	**A.** No Options **F1.** Add Finial **F2.** Add Finial **B.** Damp Location Available in powder coat or Satin Aluminum finish. **EL.** Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. **P.** Perforated Top Lens INC only Multi-circuiting available upon request.	Standard overall height shown by model no. For custom overall height, specify in inches.
GL-2171 21lbs B in 24" mm 610 10 kg W in 30" mm 765 D in 6 1/2" mm 165 H in 34" mm 865	**IN3.** 3MED **L60.** 6LED30 **L65.** 6LED35 **L64.** 6LED40					
GL-2172 29lbs B in 30" mm 760 13kg W in 36" mm 915 D in 7" mm 180 H in 38" mm 965	**IN6.** 6MED **L90.** 9LED30 **L95.** 9LED35 **L94.** 9LED40					
GL-2173 37lbs B in 38" mm 965 17kg W in 44" mm 1120 D in 8 1/2" mm 215 H in 42" mm 1070	**IN6.** 6MED **L120.** 12LED30 **L125.** 12LED35 **L124.** 12LED40					

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Lamp Definition

Code	Lamp	Type	Lamp Base
IN3, IN6	Med	A-19	Medium 120V

Code	Total Wattage	Kelvin	Delivered Lumens	CRI
L50	65	3000	8971	+90
L55	65	3500	8971	+90
L54	65	4000	8971	+90

Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.

Code	Total Wattage	Kelvin	Delivered Lumens	CRI
L60	78	3000	10544	+90
L65	78	3500	10544	+90
L64	78	4000	10544	+90
L90	118	3000	16400	+90
L95	118	3500	16400	+90
L94	118	4000	16400	+90
L120	157	3000	21794	+90
L125	157	3500	21794	+90
L124	157	4000	21794	+90

© Gross Chandelier Co.
G Lighting reserves the right to modify existing designs to improve appearance or function
G Lighting products are union made.