
STONE

Exterior Pendant

G Lighting
9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000
sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.
LED Dimming: Standard 1% 0-10V dimming.
Listing: ETL listed for wet locations.
Canopy: Matches fixture finish. Hanger 3 includes 10.125“ dia by 2.625” H spinning.
Driver: Max remote driver installation distance 25ft from fixture body.
Acrylic: Acrylic is UL-94 HB Flame Class rated.
Finish: Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.
Surge Protection: External surge protector provided as standard.





SAMPLE CATALOG NUMBER:

GL-5370- E- BLK- 1- A 036

MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-5370 W 21” 8lbs B 11 1/4” 3.6kg H 36”	**A.** 15LED30 **B.** 15LED35 **C.** 15LED40 **D.** 26LED30 **E.** 26LED35 **F.** 26LED40 **G.** 39LED30 **H.** 39LED35 **I.** 39LED40	Standard: Powder Coat **BLK**-Black **BL**-Blue **GR**-Gray **LG**-Light Gray **BE**-Beige **PAB**-Antique Brass **PA**-Painted Aluminum **PTC**-Painted Copper **WH**-White **DBZ**-Dark Bronze **NSN**-New Satin Nickel **BRN**-Brown **RD**-Red **CH**-Champagne **RG**-Reed Green **SG**-Sungold **GM**-Gun Metal **POR**-Oil Rubbed Bronze **PG**-Pine Green **DO**-Deep Orange **PV**-Purple Violet **NB**-Navy Blue Textured Powder **TLV**-Light Verdigris **TWH**-Textured White **TBL**-Textured Black **TS**-Textured Silver **TBZ**-Textured Bronze **TST**-Stone	**1.** Rigid Stem Mount Remote Driver  Drivers mounted remotely **3.** Rigid Stem Mount Oversized Canopy  Drivers mounted inside oversized canopy Tie offs factory recommended. Supplied by others.	**A.** No Options **EL.** Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage	Specify overal height in inches. For stem lengths longer than 24”, consult factory

All Dimensions are nominal.

Light Source Definition

Downlight Output

Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	15LED30	15W	1538	3000	80
B	15LED35	15W	1538	3500	80
C	15LED40	15W	1538	4000	80
D	26LED30	26W	2637	3000	80
E	26LED35	26W	2637	3500	80
F	26LED40	26W	2637	4000	80
G	39LED30	39W	3956	3000	80
H	39LED35	39W	3956	3500	80
I	39LED40	39W	3956	4000	80

Universal Voltage unless otherwise specified.
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

© Gross Chandelier Co.

G Lighting reserves the right to modify existing designs to improve appearance or function

G Lighting products are union made.