# TRILOGY

## Indoor Pendant

G Lighting
9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000
sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.

**LED Dimming:** Standard 1% 0-10V dimming with LED lamping option.


**Body:** GL-2110-2113 ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.

**Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.

**Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.






Textured white pan with LED lamping

SAMPLE CATALOG NUMBER:

GL-2112- | L95- | S- | NSN- | 1- | A- | 038

| MODEL NO. | LAMPING | ACRYLIC | FINISH | HANGER | OPTION(S) | OVERALL HEIGHT |
|---|---|---|---|---|---|---|
| **GL-2110**<br>14lbs B in 18" mm 460<br>6 kg W in 23 1/2" mm 600<br>D in 7 5/8" mm 195<br>H in 29" mm 735 | **IN3.** 3MED<br>**L50.** 5LED30<br>**L55.** 5LED35<br>**L54.** 5LED40 | Standard:<br>**S.** Satin White<br>Optional:<br>**W.** White Opal<br>Acrylic is UL-94 HB Flame Class rated. | Standard:<br>Powder Coat<br>**BLK**-Black<br>**BL**-Blue<br>**GR**-Gray<br>**LG**-Light Gray<br>**BE**-Beige<br>**PAB**-Antique Brass<br>**PA**-Painted Aluminum<br>**PTC**-Painted Copper<br>**WH**-White<br>**DBZ**-Dark Bronze<br>**NSN**-New Satin Nickel<br>**BRN**-Brown<br>**RD**-Red<br>**CH**-Champagne<br>**RG**-Reed Green<br>**SG**-Sungold<br>**GM**-Gun Metal<br>**POR**-Oil Rubbed Bronze<br>**PG**-Pine Green<br>**DO**-Deep Orange<br>**PV**-Purple Violet<br>**NB**-Navy Blue<br>Textured Powder<br>**TLV**-Light Verdigris<br>**TWH**-Textured White<br>**TBL**-Textured Black<br>**TS**-Textured Silver<br>**TBZ**-Textured Bronze<br>**TST**-Stone | **1.** Stem<br>**2.** Cable<br>**3.** Arms<br>**4.** Stem Cluster<br>Custom lengths available. For heights longer than standard, additional length will be added to top stem. | **A.** No Options<br>**F1.** Add Finial<br>**F2.** Add Finial<br>**B.** Damp Location<br>Available in powder coat or Satin Aluminum finish.<br>**EL.** Emergency LED<br>Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only.<br>**W.** White Opal Top Lens<br>INC only<br>**C.** Clear Top Lens<br>INC only<br>**P.** Perforated Top Lens<br>INC only<br>Multi-circuiting available upon request. | Standard overall height shown by model no.<br>For custom overall height, specify in inches. |
| **GL-2111**<br>21lbs B in 24" mm 610<br>10 kg W in 29 1/2" mm 750<br>D in 8 5/8" mm 220<br>H in 34" mm 865 | **IN3.** 3MED<br>**L60.** 6LED30<br>**L65.** 6LED35<br>**L64.** 6LED40 | | | | | |
| **GL-2112**<br>29lbs B in 30" mm 760<br>13kg W in 36 5/8" mm 930<br>D in 9 5/8" mm 245<br>H in 38" mm 965 | **IN6.** 6MED<br>**L90.** 9LED30<br>**L95.** 9LED35<br>**L94.** 9LED40 | | | | | |
| **GL-2113**<br>37lbs B in 38" mm 965<br>17kg W in 46" mm 1170<br>D in 11 1/8" mm 285<br>H in 42" mm 1070 | **IN6.** 6MED<br>**L120.** 12LED30<br>**L125.** 12LED35<br>**L124.** 12LED40 | | | | | |

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

### Lamp Definition

| Code | Lamp | Type | Lamp Base |
|---|---|---|---|
| IN3, IN6 | Med | A-19 | Medium 120V |

| Code | Total Wattage | Kelvin | Delivered Lumens | CRI |
|---|---|---|---|---|
| L50 | 65 | 3000 | 8971 | +90 |
| L55 | 65 | 3500 | 8971 | +90 |
| L54 | 65 | 4000 | 8971 | +90 |

Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.

| Code | Total Wattage | Kelvin | Delivered Lumens | CRI |
|---|---|---|---|---|
| L60 | 78 | 3000 | 10544 | +90 |
| L65 | 78 | 3500 | 10544 | +90 |
| L64 | 78 | 4000 | 10544 | +90 |
| L90 | 118 | 3000 | 16400 | +90 |
| L95 | 118 | 3500 | 16400 | +90 |
| L94 | 118 | 4000 | 16400 | +90 |
| L120 | 157 | 3000 | 21794 | +90 |
| L125 | 157 | 3500 | 21794 | +90 |
| L124 | 157 | 4000 | 21794 | +90 |

© Gross Chandelier Co.

G Lighting reserves the right to modify existing designs to improve appearance or function

G Lighting products are union made.